

JLG 1932R Scissor Lift

Power Source:

- Electric-powered
- 24V DC battery system

⇒Platform Capacity:

- Maximum Platform Capacity: 600 lbs (272 kg)
- Platform Extension Capacity: 250 lbs (113 kg)

- Maximum Working Height: 25 ft (7.62 m)
- Platform Height: 19 ft (5.79 m)

Nimensions:

- Overall Length: 6 ft 6 in (1.98 m)
- Overall Width: 2 ft 8 in (0.81 m)
- Overall Height (Rails Folded): 6 ft 6 in (1.98 m)
- Overall Height (Rails Extended): 6 ft 6 in (1.98 m)
- Platform Size (L x W): 5 ft 10 in x 2 ft 6 in (1.78 m x 0.76 m)

Weight:

• Machine Weight: 2,754 lbs (1,250 kg)

✓ Performance:

- Drive Speed (Stowed): 2 mph (3.2 km/h)
- Drive Speed (Raised): 0.5 mph (0.8 km/h)
- Gradeability: 25%
- Turning Radius (Inside): 0
- Turning Radius (Outside): 5 ft (1.52 m)
- Raise/Lower Time: 21/19 seconds
- Maximum Tilt Level: 3 degrees

Features:

- Electric drive system for quiet and emission-free operation
- Narrow design for easy maneuverability in tight spaces
- Compact dimensions allow transport in elevators and narrow doorways
- Roll-out extension deck for increased workspace and reach
- Variable speed rear wheel hydraulic drive for smooth operation
- Dual front-wheel drive for enhanced traction on rough terrain
- Onboard diagnostics and battery charge indicator for easy maintenance
- Swing-out battery box and removable platform control box for convenient access