

SPECIFICATIONS

Performance	MT100
Rated Operating Capacity	1000 lb. (453 kg) ¹ 1060 lb. (480 kg) ²
Carry Position ROC*	1339 lb. (607 kg)
Tipping Load	2898 lb. (1314 kg)
Hydraulic Pump Capacity	12.0 gpm (45.4 L/min.)
Travel Speed (forward)	4.1 mph (6.6 km/hr.)
Travel Speed (reverse)	2.9 mph (4.7 km/hr.)
Operating Weight (with bucket)	3390 lb. (1537 kg)
Ground Pressure	5.2 psi (35.8 kPa)
Ground Pressure (with wide tracks)	3.9 psi (27.3 kPa)
Dimensions	
Length (without bucket)	84.5 in. (2145 mm)
Width (with bucket)	36.0 in. (914 mm)
Height	54.6 in. (1387 mm)
Height to Bucket Pin	80.9 in. (2056 mm)
Engine	
Model/Emissions Tier (EPA)	D902 E4B/Tier 4
Fuel/Cooling	Diesel/Liquid
Cylinders	3
HP/Displacement	24.8 hp (18.5 kW)/55.0 cu. in. (0.9 L)
Fuel Tank Capacity	7.0 gal. (26.5 L)
Operation	
Steering and Drive	ISO joystick
Lift and Tilt	ISO joystick
Transmission	Hydrostatic track drive system
Attachment	Single lever with dual direction detent
Machine Features and Options	
Attachment Control Kit	Opt
Attachment Mounting System Conversion Kit (convert from CII to Bob-Tach System)	Opt
Auxiliary Hydraulics	Std
Case Drain Kit	Opt
Catalytic Exhaust Purifier	Opt
Choice of Attachment Mounting System	Bob-Tach mounting system or common industry interface (CII) system
Continuous Flow Shutoff Lever	Std
Engine Block Heater	Opt
Gauges/Warning Lights	Std
Hydrostatic Drive Train	Std
Lift Arm Lockout With Manual Bypass	Std
Lift Arm Support	Std
Lift Hook Locations	Std
Light Kit	Opt
Liquid-Cooled Diesel Engine	Std
Multi-Bar Lug Track	Opt
Neutral Start Interlocks	Std
Non-Marking Tracks	Opt
Parking Brake	Std
Removeable Counterweight	Std
Ride-On Platform	Std
Shutdown Kit	Opt
Spark Arrestor Muffler	Std
Tie-Down Locations	Std
Tilt Lockout	Std
Track (7 in. wide)	Std
Track (10 in. wide)	Opt

¹Counterweights located in the undercarriage.

²Counterweights located in rear position.

*Carry Position ROC is measured as 35% of tipping load when the lift arm is raised 6° and bucket is fully rolled back.

Perfect for Rental Fleets

With their job-proven technology, easy maintenance, simple controls and impressive performance, Bobcat mini track loaders are perfect for rental applications. Mini track loaders have a smaller, less-intimidating profile than some other compact equipment models. Additionally, they have easy-to-use controls and an impressive rated operating capacity of 1,000 pounds.

Incredible Versatility

Bobcat mini track loaders aren't just for lifting heavy loads. The hydraulic quick couplers make connecting and disconnecting from hydraulic attachments fast and easy. These machines are designed to run a variety of hydraulic attachments efficiently.

Attachment Flexibility

The MT100 is available with our industry-leading Bob-Tach attachment mounting system. You can also choose the common industry interface (CII) to utilize your existing mini track loader attachments.

Parts and Service Backup

With every Bobcat product, you get the support of a worldwide network of dealers offering industry-leading attachments, accessories and parts availability. Their factory-trained technicians are equipped to handle all your parts and service requirements, including engine and hydrostatic/hydraulic components.

Unbeatable Bobcat Warranty

The best equipment carries the best warranty! The MT100 mini track loader comes with a full one-year warranty with unlimited hours.

Operator Training

Ensure safe and effective operation techniques with owner and operator safety videos and training. Find them on the Bobcat Owner Portal (my.Bobcat.com).

MT100 Dimensions:

